OPTIMA

THERMAL RECEIPT PRINTER
P250

Flexible & Compact

The Optima P250 is one of our most compact Thermal Receipt Printers using 57mm (2 1/4") paper size with a rich communication interface. The modern minimalistic cube design allows for easy desktop placement. It's engineered for reliability to meet the demands of retailers large and small making it perfect for commercial retail and restaurant applications.

Ultra-High Speed with Auto Cutter

Designed and conceived to suit any and all environments, the Optima P250 is equipped with an auto paper-cutter and an ultra-fast printing speed reaching 250mm / per second and fast and easy paper roll loading design.

Back

Interface

Front

Small & Portable

The small, sleek, compact cube design fits on any desktop and allows workers to carry and operate the printer with ease.

Versatile Connectivity

The P250 is a reliable and versatile printer that comes standard with 3 built in ports including USB, Serial and Ethernet.

Drop-in-Paper loading

A simple drop-in-paper loading means that even inexperienced operators can easily maintain and load paper rolls with minimum of effort.

Key Features

✓ All interfaces supported: Serial/USB/ Ethernet port

✓ 57mm (2 1/4") paper size

✓ Ultra-high speed 250mm/per second

✓ Perfect for Retail, Restaurant and Industrial applications

✓ Modern cube design for great desktop placement

✓ High-quality thermal printing

✓ Easy paper-roll installation,

✓ Auto-cutter(1000000 times cutting)

✓ Small, lightweight and portable

✓ Supports cash drawer connection

Printer

Print Method: Thermal line printing

Print Speed: 250mm/second

Print Resolution: 203 dpi

Print Parameters: Download Logo trademark supported

Print Width: 57.5 x 0.5mm

Effective Print Width: 72mm

Max. External Diameter: 80mm

Print Command: Compatible with Esc/POS

Cutter: Includes Paper Cutter (Life 1,000,000 times)

Character: ANK character set, Chinese GB2312, traditional Chinese BIG5, 12 x 24 dots, 24 x 24 dots, 48 Columns

Buffer: Data Receiving Buffer 16KB
Flash Memory 16Mbit

Specifications

Dimensions: (D) 138.4 x (W) 120.5 x (H)123.3mm

Weight: 2.60kg

Interface Connectivity

Serial port

USB

Ethernet

General Features

Power: DC24V/2A

Cash Drawer : 1 port (compatible with EPSON)

Temperature: 0-40˚C

Contrast Humidity: 5-85˚C

Drivers: Windows 7, Windows 10, Windows 11

Certificate: CE FCC CCC ISO9001:2008

Barcode type: UPC-A,UPC-E,Code 128,EAN 128, Jan8, Jan13(EAN), Interleaved 2 of 45, Codabar

OPTIMA GROUP

1415 Pembina Highway, Winnipeg, MB, Canada, R3T 2C2   Tel: (204) 488-2274   Fax: (204) 488-3923
Email: sales@optimagopos.ca   Website: www.optimagopos.ca